MAKO 4x

Versatile violet CTP that is chem-free ready and capable of imaging up to a 6-page press

The MAKO 4x is the latest evolution in the MAKO CTP family, and one of the first Violet CTP devices in the world to offer commercial printers a clear path to chemistry-free technology. The MAKO 4x represents ECRM's highest quality imaging output with resolution sets from 1200 – 3556 dpi, and is one of the fastest 4-page CTP units in its class, imaging over 19 Speedmaster 74 plates per hour at 2400 dpi.

- Utilizing the latest 120 mw violet laser technology our future-proof design allows a smooth transition to violet chemistry-free plate technology.
- The MAKO 4x employs an auto-pinch/auto-image feature for true hands-free operation after initial plate positioning.

- ECRM's versatile platesetter technology provides ultimate format flexibility that's ideal for multi-press sites.
- Expanded format capability images from 228mm x 252mm (8.9" x 9.9") to 660mm x 960mm (26.0" x 37.8").
- Flexible ECRM's patented press registration pin bars allow for both edge and notch registration, matching a wider range of press requirements.
- No hidden extras our online conveyor is standard on all MAKO CTP, allowing for a direct connection to the processor at no extra cost.
- Uses a straight-through plate path for easy operation and automated delivery to the processor.
- Bundled with CtServer Professional ECRM's enhanced 1-bit TIFF server. Our open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- Simple and intuitive operator interface makes training easy.
- Basic electricity requirements and quick installation no dedicated power line needed. Low energy consumption, draws the same energy as a PC.



imaging systems

Choose ECRM for your Violet CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



| Plate Sizes | Maximum: 660mm x 960mm (26.0" x 37.8") Minimum: 228mm x 252mm (8.9" x 9.9") |
|----------------------|--|
| Plate Thickness | 0.14mm to 0.35mm (0.0055" to 0.014") |
| Media Types | Violet-sensitive photopolymer and silver halide metal plates. See media specifications for safe-light information. |
| Recording Source | 120 mw violet laser diode (405 nm) |
| Resolutions | Seven resolutions from 1200 to 3556 dpi (472 to 1400 dpcm) Resolutions include; 1200, 1270, 1800, 2400, 2540, 3048, and 3556dpi |
| Maximum Line Screen | Up to 200 lpi (78.7 lpcm). Media dependent |
| Repeatability | 0.025mm (0.001") typical. May vary according to media type and processing conditions |
| Processing | Online: The plate transport automatically moves the plate into the processor. |
| Environmental | Power: 100 - 240 Volts; 3 Amps; 250 watts maximum; 50/60Hz, single phase Heat Dissipation: 850 BTU/hour |
| Interface | USB 2.0 High Speed. 3 meter host cable provided. |
| Operating Conditions | 62 - 86° F (17 - 30° C); relative humidity 45 - 65%, non-condensing. Relative humidity outside of this range may affect performance. Operating conditions outside plate media specifications may affect performance. |
| Weight | 145.5 kg (320 lbs.) |
| Footprint Dimensions | Width: 96.5cm (38.0") Length: 185.4cm (73.0") Height: 188.0cm (74.0") |

MAKO 4x Specifications

ECRM[®] imaging systems

| Headquarters: 554 Clark Road Tewksbury, MA 01876 USA Tel: (+1) 978.851.0207 Fax: (+1) 978.851.7016 sales@ecrm.com www.ecrm.com | International Sales Offices:3 Century Court, Tolpits Lane Watford, Hertfordshire WD18 9PU, UKB2, 10/F, Block B, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong Tel: (+44) 1923.218.256 Fax: (+44) 1923.218.256 sales_uk@ecrm.comTel: (+852) 2564-8989 Fax: (+852) 2564-8821 sales_hk@ecrm.com sales_asia@ecrm.com |
|---|---|
|---|---|

All ECRM products carry the CE mark. All products are NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.